

DP-7328 Differential Voltage Probe

SPECIFICATIONS:

FUNCTION / MODEL	DP-7328
Bandwidth (-3dB)	DC-to 30 MHZ
Differential Voltage: DC + AC peak	X 20 : ≤ 140 V X 200 : ≤ 1400 V
Common Mode Voltage DC	$\leq \pm 1400$ V (DC+AC peak)
Common Mode Voltage AC	≤ 990 Vrms
Range (Switchable)	2 Range: X 20, X 200
Input Impedance (Between)	10 M Ω // 1 PF
Each Input to Ground	5 M Ω // 2 PF
Accuracy	$\leq \pm 2\%$
Output Impedance	50 Ω (for 1 M Ω Input Oscilloscope)
Rise Time	≈ 14 nS
Output Voltage	$\leq \pm 7$ V
Rejection Rate on Common Mode	60 Hz > 70 dB, 100Hz > 60 dB, 1MHz > 50dB
Power Supply	External 5 V DC (USB Input), consumption about 300 mA

ACCESSORIES:



PINTEK

Pintek Electronics Co., Ltd

2F No.32 Tai-Pen Rd., Shulin Dist., New Taipei City, Taiwan

Tel: 886-2-86859562~3 ; 886-2-86861898

Fax: 886-2-86852081 ; 886-2-86861114

<http://www.pintek.com.tw>

E-Mail : pintek@pintek.com.tw ; pintek@ms26.hinet.net

SALES AGENT